



Swivel Range TEN GROUP

Swivels



Part no. Various

- Swivels for connecting pulling rope to cable sock
- For Overhead or Underground application
- Chamfered edges allowing safe and smooth passage of conductor through rollers



Part Number	Picture	Max Rope Size OD (mm)	WLL* (kg)	Diameter OD (mm)	Overall Length mm	Made From	Features	Weight KG Each
A-1.8		7.9	816	22.2	77.7	Corrosion protected alloy steel	Precision components, perform well under severe loading conditions	0.14
BB-4		15.0	1,814	31.7	115.0			0.42
GGT001		10.0	2,333	28.0	106.0	High tensile galvanised and corrosion protected steel.	Special design can bare high radial loads. Thrust bearings designed to avoid torsion strain accumulation.	0.3
GGT010		13.0	3,666	40.0	143.0			0.9
GGT020		18.0	7,333	54.0	184.0			2.1
GGT030		24.0	12,000	60.0	234.0			3.4
GGT040		28.0	25,000	77.0	322.0			8.2
GGT180		32.0	25,000	81.0	336.0			8.7
72294		60.0	7,500	60	220.0	Corrosion protected alloy steel	15° Vertical flexibility.	3.2

*Based on 3:1 safety factor

Other swivel types available upon request

Breakaway



Various UG



Leaders



TEN Group Australia

QLD : 2/186 Granite St
 NSW : 6/15-17 Ace Cres
 VIC : 12 Dunlopillo Dve
 WA :

GEEBUNG 4034
 TUGGERAH 2259
 DANDENONG STH 3175
 PERTH 6163

P | F +61 7 3212 8999 | 8998
 P | F +61 2 4351 5400 | 5411
 P | F +61 408 228 473
 P | F +61 488 275 928

www.tengroup.com.au **1300 ASK TEN**

TEN Group New Zealand

NTH : 4/630 Great South Rd
 STH :

Papatoetoe, AUCKLAND
 Rangiora, CHRISTCHURCH

P | F +64 9 270 0007 | 0009
 P | F +64 21 412 420

www.tengroup.co.nz **0800 ASK TEN**