

Stringing Accessories - Socks & Swivels



Single Large Eye – Heavy Duty Socks

- Suitable for transmission and distribution
- Colour coded plastic bands at ferrule to identify range and capacity
- Steel wires with protective finish and alloy ferrule

Part No	Suitable Swivel	Conductor OD	Colour	Break Load	Weight
GCT001	GGT001	8 - 17mm	Yellow	35kN	0.7kg
GCT010	GGT010	17 - 29mm	Red	85kN	1.3kg
GCT020	GGT020	29 - 38mm	Green	130kN	2.1kg
GCT030	GGT020, GGT030	38 - 50mm	Black	180kN	2.7kg

Double Head Socks

- Suitable for transmission and distribution
- Colour coded plastic bands at ferrule to identify range and capacity
- Steel wires with protective finish and alloy ferrule

Part No	Conductor OD	Colour	Break Load	Weight
GCT500	8 - 17mm	Yellow	35kN	1.15kg
GCT510	17 - 29mm	Red	85kN	2.3kg
GCT520	29 - 38mm	Green	130kN	3.6kg
GCT530	38 - 50mm	Black	180kN	4.8kg

Underground Socks

- Suitable for single and multiple core underground cables
- Longer socks give extra pulling force - larger surface area gives better grip
- Sheaths protect strands at the end of the sock from rubbing on the bare conductor
- Steel wires with protective finish and alloy ferrule offering durability and longevity

Part No	Suitable Swivel	Conductor OD	Length	Break Load	Weight
GCL180	GGT001	46-60mm	1.6m	50kN	2.0kg
GCL190	GGT001	61-80mm	1.8m	80kN	2.5kg
GCL200	GGT010	81-100mm	2.0m	100kN	3.0kg
GCL210	GGT010	101-140mm	2.0m	100kN	3.5kg

Standard Swivels

- Swivels for connecting pulling rope to cable sock
- For Overhead or Underground application
- Made from high tensile galvanised and corrosion protected steel
- Chamfered edges allowing smooth passing through rollers or conduit
- Special design can bear high radial loads. Thrust bearings designed to avoid torsion strain accumulation

Part No	Max Rope OD	Break Load	Swivel OD	Length	Weight
GGT001	10mm	70kN	28mm	106mm	0.3kg
GGT010	13mm	110kN	40mm	143mm	0.9kg
GGT020	18mm	220kN	54mm	184mm	2.1kg
GGT030	24mm	360kN	60mm	234mm	3.4kg
GGT040	28mm	750kN	77mm	322mm	8.2kg

