

12T Crimping Dies

12 Tonne Dies

Part No: K12-

- Crimping dies to suit hydraulic battery and hand hydraulic 12T "C" type crimpers.
- Commonly referred to as "C" or "U" type dies.
- Dies colour coded to material type.
- Finished A/F diameter marked on die face for easy identification on finished lug or sleeve.



12T Crimping Tool
EK12042-LAU

Part No	Type	Conductor Type (mm ²)	A/F (mm)	Width (mm)	Finish
K12-04.4-CU	Copper	6mm ²	4.4	6.5	Gold
K12-05.7-CU	Copper	10mm ²	5.7	6.5	Gold
K12-06.3-CU	Copper	16mm ²	6.3	17.5	Gold
K12-07.7-CU	Copper	25mm ²	7.7	17.5	Gold
K12-08.2-CU	Copper	-	8.2	9	Gold
K12-09.2-CU	Copper	35mm ²	9.2	17.5	Gold
K12-10.4-CU	Copper	50mm ²	10.4	17.5	Gold
K12-11.5-CU	Copper	70mm ²	11.5	17.5	Gold
K12-13.0-CU	Copper	OH 37/.064-19/2.11	13.0	17.5	Gold
K12-13.2-CU	Copper	OH 19/1.70	13.2	-	Gold
K12-14.2-CU	Copper	95mm ²	14.2	17.5	Gold
K12-14.8-CU	Copper	OH 19/2.00-19/2.11	14.8	9	Gold
K12-16.5-CU	Copper	120mm ²	16.5	14	Gold
K12-18.3-CU	Copper	150mm ²	18.3	14	Gold
K12-19.0-CU	Copper	-	19.0	22	Gold
K12-19.3-CU	Copper	OH 19/2.57	19.3	14	Gold
K12-20.0-CU	Copper	185mm ²	20	14	Gold
K12-22.0-CU	Copper	-	22.0	10	Gold
K12-23.1-CU	Copper	240mm ²	23.1	10	Gold
K12-26.0-CU	Copper	300mm ²	26.0	10	Gold
K12-28.1-CU	Copper	400mm ²	28.1	10	Gold
K12-09.0-AL	Aluminium	6-35mm ²	9.0	22	Silver
K12-13.2-AL	Aluminium	50-70mm ²	13.2	22	Silver
K12-14.0-AL	Aluminium	OH 7/2.25	14.0	22	Silver
K12-14.5-AL	Aluminium	OH 7/2.50	14.5	22	Silver
K12-14.8-AL	Aluminium	OH 19/2.00-19/2.11	14.8	22	Silver
K12-16.6-AL	Aluminium	-	16.6	22	Silver
K12-17.3-AL	Aluminium	95 - 120mm ²	17.3	22	Silver
K12-18.0-AL	Aluminium	OH 7/3.00 to 7/3.75	18.0	22	Silver
K12-19.0-AL	Aluminium	OH 7/4.50	19.0	22	Silver
K12-21.0-AL	Aluminium	suits Utilux 150-185mm ²	21.0	18	Silver
K12-21.5-AL	Aluminium	-	21.5	18	Silver
K12-22.0-AL	Aluminium	150-185mm ²	22.0	18	Silver
K12-23.1-AL	Aluminium	-	23.1	18	Silver
K12-24.9-AL	Aluminium	-	24.9	18	Silver
K12-25.4-AL	Aluminium	OH 19/3.75 CABAC	25.4	18	Silver
K12-26.2-AL	Aluminium	OH 19/3.75 Utilux	26.2	18	Silver
K12-28.4-AL	Aluminium	240-300mm ²	28.4	18	Silver
K12-30.0-AL	Aluminium	-	30.0	18	Silver
K12-30.3-AL	Aluminium	OH 19/4.75	30.3	18	Silver
K12-14.0-ABC	ABC	25mm ²	14.0	9	Black
K12-17.3-ABC	ABC	35-70mm ²	17.3	9	Black
K12-21.5-ABC	ABC	95-150mm ²	21.5	9	Black

12T Crimping Dies

12 Tonne Dies cont.



Part No	Type	Conductor Type (mm ²)	A/F (mm)	Width (mm)	Finish
K12-06.8-ST	Steel	Inner Steel ACSR	6.8	10	Black
K12-07.5-ST	Steel	Inner Steel ACSR	7.5	10	Black
K12-09.5-ST	Steel	Inner Steel ACSR	9.5	10	Black
K12-07.5-CS	Cu Screen	-	7.5	16	Gold
K12-12.7-CS	Cu Screen	-	12.7	14	Gold
K12-14.0-CS	Cu Screen	-	14	18	Gold
K12-09.2-CUOH	Copper	OH 7/2.00-7/2.03	9.2	9	Gold
K12-A-INDENT-16	Aluminium	120, sector cable, 3 or 4 core	-	-	Silver
K12-A-INDENT-18	Aluminium	150-185, sector cable, 3 or 4 core	-	-	Silver
K12-A-INDENT-19	Aluminium	240-300, sector cable, 3 or 4 core	-	-	Silver
K12-ANEST12	Aluminium	70-300 sector cable, 3 core	-	-	Silver
K12-ANEST14	Aluminium	70-120 sector cable, 4 core	-	-	Silver
K12-ANEST15	Aluminium	185-300 sector cable, 4 core	-	-	Silver
K12-CSFLAT9	Copper	hex / flat, 9mm crimp width, flat one side			Gold
K12-U997	"C" profile for earth rod	120, 15.9-19.05mm rods	-	-	Gold
K12-UO	"U" style, UO, compression, Burndy				
DUOT	CEC connector, profile C, high fault current capacity, heavy duty				

