



NAGAKI



RICKY-2

Chain Hoists 0.75 and 1.5T - Nagaki (NGK)

Part No. RICKY-2 & RICKY-3

- Lightweight aluminium housing with 5mm OD alloy chain link & forged hooks
- 1.5m pull
- 360° rotating handle of 230mm length
- Safety hook attachment
- All models manufactured under ISO9001 and ISO14001 standards

Suitable for Pulling/Tensioning

Part No.	Style	WLL (T)	Chain length (m)	Min Pull (mm)	Max Pull (mm)	Handle Length (mm)	Wt (kg)
RICKY-2	Safety Hook	0.75	1.5	300	1800	230	4
RICKY-3	Safety Hook	1.5		350	1850	230	5

Chain Hoists 3, 4 and 6T - Nagaki (NGK)

Part No. Various

- Lightweight aluminium housing with 5mm OD alloy chain link & forged hooks
- 360° rotating handle of 430mm length
- Safety hook attachment
- Special length chains available on request
- Model2000C with Torque Handle

Suitable for Pulling/Tensioning



MODEL3000

Part No.	Style	WLL (T)	Chain length (m)	Min Pull (mm)	Max Pull (mm)	Handle Length (mm)	Wt (kg)
MODEL2000C-1.5	Safety Hook	2	1.5	480	2000	430	6.6
MODEL3000-1.5	Safety Hook	3		480	2000	430	8
MODEL4000H-1.5	Safety Hook	4		580	2180	430	12
MODEL6000-1.5	Clevis	6		650	2250	430	19

Other chain lengths available - Contact TEN for further information

Model 4000 lightweight & ideal for Transmission tensioning



Nagaki utilise Japanese Technology to protect the quality stipulated by their company standards

Constant research and development to meet the demands and expectations of the professionals that operate their products everyday.

