



Hydraulic Hoses - Low Pressure & High Pressure



Protective Dust
Caps Included



Low Pressure Hydraulic Hoses

- 2,250 PSI Low pressure twin line flexible hydraulic hose
- Clear strain relief sleeve over crimped connections
- Manufactured for use in extreme temperatures -40°C to 100°C
- Certified non-conductive highly flexible rubber
- Impulse tested higher than SAE requirements
- Supplied with flush face couplers with protective dust caps
- Neoprene inner tube with nitrile outer, reinforced two textile braid
- Electrical Test - 75kV/3min (>100µA)
- Tested to have passed a total hazard current test of 75kV for 3 minutes with current not exceeding 100 micro amps per 300mm

Part No	Colour	Length	Max Operating Pressure	Min Burst Pressure	Electrical Test	Hose ID	Weight
REL-2250-3-O-TEN	Orange	3m	2,250 PSI	9,000 PSI	75kV/3min (>100µA)	9.5mm	2.85kg
REL-2250-3-TEN	Red	3m	2,250 PSI	9,000 PSI	75kV/3min (>100µA)	9.5mm	2.85kg

Everything
Hydraulics!



**RELIABLE
EQUIPMENT**

CRAFTED WITH PRIDE IN THE U.S.A.
USED WITH CONFIDENCE AROUND THE WORLD



**Protect
Equipment and
Workers**

In-line Flow Pressure Gauge

Part No: REL-FPG

- Protect workers, valuable equipment, and property from damage caused by excess hydraulic pressure or flow
- Install between tool and hydraulic power source to test system output pressure and hydraulic flow
- Allows you to determine correct system pressure and hydraulic flow to the tool, reducing seal wear and extending the life and performance of your low pressure hydraulic tools

**Single and Double
Hydraulic Hose
Assemblies Available**



**Highly
Flexible**

Protective Dust
Caps Included

High Pressure Hydraulic Hose

TEN Part No: REL-3VE4-3-TEN

- 10,000 PSI High pressure flexible hydraulic hose
- Strain relief sleeve over crimped connections
- Safety orange jacket
- Certified non-conductive highly flexible rubber
- Impulse tested higher than SAE requirements
- Supplied with male 3/8" snap on couplers with protective dust caps
- H/D Thermoplastic construction, certified nonconductive, lightweight, wear-resistant, excellent weatherability
- Manufactured for use in extreme temperatures

Length	Max Operating Pressure	Min Burst Pressure	Hose ID	Weight
3m	10,000 PSI	40,000 PSI	1/4" (6.35mm)	2kg

