



SAFETY DATA SHEET

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name H.M. GLOSS RESTORER KIT (C400-1520, PART B)
Synonyms C400-1520 - STOCK CODE(S) • H.M. GLOSS RESTORER KIT - PART B • PART B, GLOSS RESTORER KIT • THE ENERGY NETWORK GLOSS RESTORER KIT

1.2 Uses and uses advised against

Uses EPOXY RESIN SYSTEM • GLOSS RESTORER • HARDENER
This product is used in conjunction with H.M. GLOSS RESTORER KIT - PART A. Please consult the appropriate SDS before use.

1.3 Details of the supplier of the product

Supplier name THE ENERGY NETWORK (AUST) PTY LTD
Address 2B / 605 Zillmere Road, Zillmere, QLD, 4034, AUSTRALIA
Telephone (07) 3212 8999
Fax (07) 3212 8998
Email sales@tengroup.com.au
Website <http://www.tengroup.com.au>

1.4 Emergency telephone numbers

Poison Information 13 11 26
Centre

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

Physical Hazards

Flammable Liquids: Category 3

Health Hazards

Acute Toxicity: Oral: Category 4
Aspiration Hazard: Category 1
Acute Toxicity: Skin: Category 4
Skin Corrosion/Irritation: Category 2
Skin Sensitisation: Category 1
Serious Eye Damage / Eye Irritation: Category 1
Acute Toxicity: Inhalation: Category 4
Specific Target Organ Toxicity (Single Exposure): Category 3 (Respiratory Irritation)
Carcinogenicity: Category 1
Toxic to Reproduction: Category 1
Specific Target Organ Toxicity (Repeated Exposure): Category 2

Environmental Hazards

Not classified as an Environmental Hazard

2.2 GHS Label elements

Signal word DANGER

PRODUCT NAME H.M. GLOSS RESTORER KIT (C400-1520, PART B)**Pictograms****Hazard statements**

| | |
|------|--|
| H226 | Flammable liquid and vapour. |
| H302 | Harmful if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H312 | Harmful in contact with skin. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H332 | Harmful if inhaled. |
| H335 | May cause respiratory irritation. |
| H350 | May cause cancer. |
| H360 | May damage fertility or the unborn child. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |

Prevention statements

| | |
|------|--|
| P201 | Obtain special instructions before use. |
| P202 | Do not handle until all safety precautions have been read and understood. |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P233 | Keep container tightly closed. |
| P240 | Ground and bond container and receiving equipment. |
| P241 | Use explosion-proof electrical/ventilating/lighting equipment. |
| P243 | Take action to prevent static discharges. |
| P260 | Do not breathe dust/fume/gas/mist/vapours/spray. |
| P264 | Wash thoroughly after handling. |
| P270 | Do not eat, drink or smoke when using this product. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P272 | Contaminated work clothing should not be allowed out of the workplace. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. |

Response statements

| | |
|--------------------|--|
| P303 + P361 + P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. |
| P304 + P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. |
| P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P308 + P313 | IF exposed or concerned: Get medical advice/ attention. |
| P310 | Immediately call a POISON CENTRE or doctor/physician. |
| P321 | Specific treatment is advised - see first aid instructions. |
| P330 | Rinse mouth. |
| P331 | Do NOT induce vomiting. |
| P362 + P364 | Take off contaminated clothing and wash it before reuse. |
| P370 + P378 | In case of fire: Use appropriate media to extinguish. |

Storage statements

| | |
|--------------------|---|
| P403 + P233 + P235 | Store in a well-ventilated place. Keep cool. Keep container tightly closed. |
| P405 | Store locked up. |

Disposal statements

| | |
|------|--|
| P501 | Dispose of contents/container in accordance with relevant regulations. |
|------|--|

2.3 Other hazards

No information provided.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

| Ingredient | CAS Number | EC Number | Content (w/w) |
|---|------------|-----------|---------------|
| XYLENE | 1330-20-7 | 215-535-7 | 40 to 70% |
| FATTY ACIDS, C18-UNSATD., DIMERS, OLIGOMERIC REACTION PRODUCTS WITH TALL-OIL FATTY ACIDS AND TRIETHYLENETETRAMINE | 68082-29-1 | 500-191-5 | 10 to 30% |
| 2-BUTOXYETHANOL | 111-76-2 | 203-905-0 | 7 to 13% |
| ETHYLBENZENE | 100-41-4 | 202-849-4 | 7 to 13% |

PRODUCT NAME H.M. GLOSS RESTORER KIT (C400-1520, PART B)

| | | | |
|-------------|---|---|-----------|
| ADDITIVE(S) | - | - | Remainder |
|-------------|---|---|-----------|

4. FIRST AID MEASURES

4.1 Description of first aid measures

| | |
|-----------------------------|--|
| Eye | If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes. |
| Inhalation | If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or an Air-line respirator (in poorly ventilated areas). Apply artificial respiration if not breathing. |
| Skin | If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor. |
| Ingestion | For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting. Rinse mouth out with water and give plenty of water to drink. |
| First aid facilities | Eye wash facilities and safety shower should be available. |

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Dry agent, carbon dioxide or foam. Prevent contamination of drains and waterways.

5.2 Special hazards arising from the substance or mixture

Flammable. May evolve toxic gases (carbon/ nitrogen oxides, amines, ammonia, hydrocarbons) when heated to decomposition.

5.3 Advice for firefighters

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

5.4 Hazchem code

- 3Y
- 3 Alcohol Resistant Foam is the preferred firefighting medium but, if it is not available, normal foam can be used.
- Y Risk of violent reaction or explosion. Wear full fire kit and breathing apparatus. Contain spill and run-off.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

PRODUCT NAME H.M. GLOSS RESTORER KIT (C400-1520, PART B)**7.2 Conditions for safe storage, including any incompatibilities**

Store in a cool, dry, well ventilated area, removed from incompatible substances, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Large storage areas should have appropriate fire protection systems.

7.3 Specific end uses

No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**8.1 Control parameters****Exposure standards**

| Ingredient | Reference | TWA | | STEL | |
|------------------------|----------------|-----|-------------------|------|-------------------|
| | | ppm | mg/m ³ | ppm | mg/m ³ |
| 2-Butoxyethanol (EGBE) | SWA [AUS] | 20 | 96.9 | 50 | 242 |
| 2-Butoxyethanol (EGBE) | SWA [Proposed] | 10 | 49 | 50 | 242 |
| Ethyl benzene | SWA [AUS] | 100 | 434 | 125 | 543 |
| Ethyl benzene | SWA [Proposed] | 20 | 87 | -- | -- |
| Xylene | SWA [AUS] | 80 | 350 | 150 | 655 |

Biological limits

| Ingredient | Reference | Determinant | Sampling Time | BEI |
|-----------------|-----------|--|---------------|---------------------|
| 2-BUTOXYETHANOL | ACGIH BEI | Butoxyacetic acid (BAA) in urine (with hydrolysis) | End of shift | 200 mg/g creatinine |
| ETHYLBENZENE | ACGIH BEI | Sum of mandelic acid and phenylglyoxylic acid in urine | End of shift | 0.15 g/g creatinine |
| XYLENE | ACGIH BEI | Methylhippuric acids in urine | End of shift | 1.5 g/g creatinine |

8.2 Exposure controls

Engineering controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof extraction ventilation is recommended. Maintain vapour levels below the recommended exposure standard.

PPE

| | |
|--------------------|--|
| Eye / Face | Wear splash-proof goggles. |
| Hands | Wear PVA or Viton® or nitrile gloves. |
| Body | Wear coveralls. |
| Respiratory | Wear a Type A (organic vapour) / Organic vapour respirator. If sanding dry product, wear a Class P1 (particulate) / N95 respirator. If spraying, with prolonged use, or if in confined areas, wear an Air-line / Full Facepiece Supplied-Air Respirator (SAR). |

**9. PHYSICAL AND CHEMICAL PROPERTIES****9.1 Information on basic physical and chemical properties**

| | |
|-------------------------|-------------------------------|
| Appearance | CLEAR LIQUID |
| Odour | HYDROCARBON ODOUR |
| Flammability | FLAMMABLE |
| Flash point | 27°C (cc) (Approximately) |
| Boiling point | 58°C to 153°C (Approximately) |
| Melting point | NOT AVAILABLE |
| Evaporation rate | < 1 (Ether = 1) |
| pH | NOT AVAILABLE |
| Vapour density | > 1 (Air = 1) |
| Relative density | NOT AVAILABLE |

9.1 Information on basic physical and chemical properties

| | |
|---------------------------|---------------|
| Solubility (water) | NOT AVAILABLE |
| Vapour pressure | NOT AVAILABLE |
| Upper explosion limit | 15.8 % |
| Lower explosion limit | 1.0 % |
| Partition coefficient | NOT AVAILABLE |
| Autoignition temperature | NOT AVAILABLE |
| Decomposition temperature | NOT AVAILABLE |
| Viscosity | NOT AVAILABLE |
| Explosive properties | NOT AVAILABLE |
| Oxidising properties | NOT AVAILABLE |
| Odour threshold | NOT AVAILABLE |

9.2 Other information

| | |
|-------------|------|
| % Volatiles | 79 % |
|-------------|------|

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Hazardous polymerisation is not expected to occur.

10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), alkalis (e.g. sodium hydroxide), heat and ignition sources.

10.6 Hazardous decomposition products

May evolve toxic gases (carbon/ nitrogen oxides, amines, ammonia, hydrocarbons) when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity Harmful if swallowed, in contact with skin or if inhaled.

Information available for the ingredients:

| Ingredient | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|-----------------|-------------------------------|-----------------------|--------------------------|
| XYLENE | > 2000 mg/kg (rat) (AICIS) | > 1700 mg/kg (rabbit) | 20 mg/L/4h (rat) (AICIS) |
| 2-BUTOXYETHANOL | ~1200 mg/kg (rat) (ECHA) | 220 mg/kg (rabbit) | 450 mg/L/4hrs (rat) |
| ETHYLBENZENE | 3500 mg/kg (rat) | 17800 mg/kg (rabbit) | 17.8 mg/l/4 hours (rat) |

| | |
|---------------------------------|---|
| Skin | Causes skin irritation. Contact may result in irritation, redness, pain and rash. May result in burns with prolonged contact. |
| Eye | Causes serious eye damage. Contact may result in irritation, lacrimation, pain and redness. May result in burns with prolonged contact. |
| Sensitisation | May cause an allergic skin reaction. This product is not classified as a respiratory sensitiser. |
| Mutagenicity | Not classified as a mutagen. |
| Carcinogenicity | May cause cancer. Ethylbenzene is classified as possibly carcinogenic to humans (IARC Group 2B). |
| Reproductive | May damage fertility. |
| STOT - single exposure | Over exposure may result in irritation of the nose and throat, with coughing. High level exposure may result in dizziness, drowsiness and breathing difficulties. |
| STOT - repeated exposure | May cause damage to organs through prolonged or repeated exposure. |

PRODUCT NAME H.M. GLOSS RESTORER KIT (C400-1520, PART B)

Aspiration Aspiration or inhalation may cause chemical pneumonitis and pulmonary oedema.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

May cause long lasting harmful effects in the aquatic environment.

12.2 Persistence and degradability

No information provided.

12.3 Bioaccumulative potential

No information provided.

12.4 Mobility in soil

No information provided.

12.5 Other adverse effects

Avoid contamination of drains and waterways.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposal Mix parts A + B together (small amounts), absorb with sand, vermiculite or similar and dispose of to an approved landfill site. Ensure protective equipment is worn when mixing. Do not seal containers/tins until reaction is complete. Larger quantities may be incinerated at approved facility. Prevent contamination of drains and waterways as environmental damage may result. Contact the manufacturer/supplier for additional information (if required).

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



| | LAND TRANSPORT (ADG) | SEA TRANSPORT (IMDG / IMO) | AIR TRANSPORT (IATA / ICAO) |
|------------------------------------|----------------------|----------------------------|-----------------------------|
| 14.1 UN Number | 1263 | 1263 | 1263 |
| 14.2 Proper Shipping Name | PAINT | PAINT | PAINT |
| 14.3 Transport hazard class | 3 | 3 | 3 |
| 14.4 Packing Group | III | III | III |

14.5 Environmental hazards

Not a Marine Pollutant.

14.6 Special precautions for user

Hazchem code ●3Y
GTEPG 3C1
EmS F-E, S-E

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule Classified as a Schedule 5 (S5) Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

PRODUCT NAME H.M. GLOSS RESTORER KIT (C400-1520, PART B)

| | |
|---------------------------|--|
| Classifications | Safe Work Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals (GHS Revision 7). |
| Inventory listings | AUSTRALIA: AIIC (Australian Inventory of Industrial Chemicals) All components are listed on AIIC, or are exempt. |

16. OTHER INFORMATION

| | |
|-------------------------------|--|
| Additional information | <p>WELDING - SANDING - CUTTING DRIED OR CURED PRODUCT: If sanding, cutting or welding dried or cured product, adverse health effects may be avoided by the use of appropriate engineering controls and/or personal protective equipment. If welding, wear a Class P2 (Metal fume) respirator and depending on the nature of the surface being welded, additional protection (e.g. for organic vapours/acid gas) may also be required. A Class P1 (Particulate) respirator is recommended if dust is generated.</p> <p>RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.</p> <p>PERSONAL PROTECTIVE EQUIPMENT GUIDELINES: The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.</p> <p>HEALTH EFFECTS FROM EXPOSURE: It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.</p> |
|-------------------------------|--|

| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|----------------------|--|-------|---|-------|---|-----|------------------------|--------|-----------------------------------|-----|---|-----|----------------------------|-------|--------------------------------------|------|---|------|---|------|---------------------------------------|-------------------|----------------------------|-----|-----------------------------|----|---|-----|-------------------|------|---------------------------|---------|--|---------|--|-------|--|-----|---------------------|-----|-----------------------|-----|-----------------------|
| Abbreviations | <table><tr><td>ACGIH</td><td>American Conference of Governmental Industrial Hygienists</td></tr><tr><td>CAS #</td><td>Chemical Abstract Service number - used to uniquely identify chemical compounds</td></tr><tr><td>CNS</td><td>Central Nervous System</td></tr><tr><td>EC No.</td><td>EC No - European Community Number</td></tr><tr><td>EMS</td><td>Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)</td></tr><tr><td>GHS</td><td>Globally Harmonized System</td></tr><tr><td>GTEPG</td><td>Group Text Emergency Procedure Guide</td></tr><tr><td>IARC</td><td>International Agency for Research on Cancer</td></tr><tr><td>LC50</td><td>Lethal Concentration, 50% / Median Lethal Concentration</td></tr><tr><td>LD50</td><td>Lethal Dose, 50% / Median Lethal Dose</td></tr><tr><td>mg/m³</td><td>Milligrams per Cubic Metre</td></tr><tr><td>OEL</td><td>Occupational Exposure Limit</td></tr><tr><td>pH</td><td>relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).</td></tr><tr><td>ppm</td><td>Parts Per Million</td></tr><tr><td>STEL</td><td>Short-Term Exposure Limit</td></tr><tr><td>STOT-RE</td><td>Specific target organ toxicity (repeated exposure)</td></tr><tr><td>STOT-SE</td><td>Specific target organ toxicity (single exposure)</td></tr><tr><td>SUSMP</td><td>Standard for the Uniform Scheduling of Medicines and Poisons</td></tr><tr><td>SWA</td><td>Safe Work Australia</td></tr><tr><td>TLV</td><td>Threshold Limit Value</td></tr><tr><td>TWA</td><td>Time Weighted Average</td></tr></table> | ACGIH | American Conference of Governmental Industrial Hygienists | CAS # | Chemical Abstract Service number - used to uniquely identify chemical compounds | CNS | Central Nervous System | EC No. | EC No - European Community Number | EMS | Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods) | GHS | Globally Harmonized System | GTEPG | Group Text Emergency Procedure Guide | IARC | International Agency for Research on Cancer | LC50 | Lethal Concentration, 50% / Median Lethal Concentration | LD50 | Lethal Dose, 50% / Median Lethal Dose | mg/m ³ | Milligrams per Cubic Metre | OEL | Occupational Exposure Limit | pH | relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline). | ppm | Parts Per Million | STEL | Short-Term Exposure Limit | STOT-RE | Specific target organ toxicity (repeated exposure) | STOT-SE | Specific target organ toxicity (single exposure) | SUSMP | Standard for the Uniform Scheduling of Medicines and Poisons | SWA | Safe Work Australia | TLV | Threshold Limit Value | TWA | Time Weighted Average |
| ACGIH | American Conference of Governmental Industrial Hygienists | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| CAS # | Chemical Abstract Service number - used to uniquely identify chemical compounds | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| CNS | Central Nervous System | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| EC No. | EC No - European Community Number | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| EMS | Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| GHS | Globally Harmonized System | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| GTEPG | Group Text Emergency Procedure Guide | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| IARC | International Agency for Research on Cancer | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| LC50 | Lethal Concentration, 50% / Median Lethal Concentration | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| LD50 | Lethal Dose, 50% / Median Lethal Dose | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| mg/m ³ | Milligrams per Cubic Metre | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| OEL | Occupational Exposure Limit | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| pH | relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline). | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ppm | Parts Per Million | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| STEL | Short-Term Exposure Limit | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| STOT-RE | Specific target organ toxicity (repeated exposure) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| STOT-SE | Specific target organ toxicity (single exposure) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| SUSMP | Standard for the Uniform Scheduling of Medicines and Poisons | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| SWA | Safe Work Australia | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| TLV | Threshold Limit Value | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| TWA | Time Weighted Average | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

PRODUCT NAME H.M. GLOSS RESTORER KIT (C400-1520, PART B)

Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared by

Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794
Email: info@rmtglobal.com
Web: www.rmtglobal.com

[End of SDS]