



HV Switch assembly order from

Customise your HV Switch assemblies

STEP 1

Select Your Jumper/Bonder type (tick to select) ☒

<input type="checkbox"/> ALTD06200R 600A, 38kV, 200 BIL, 66kN, with hooks - CHANCE	<input type="checkbox"/> ALTD06200RL 600A, 38kV, 200 BIL, 66kN, with load break arc chute & hooks - CHANCE	Replacement Arc chute assembly PART No. E816-0228P
---	---	---

The NGK 2T Locking Grip (AL-2TON-GRIP-L) is ideal for holding conductor tension whilst installing temporary switches



STEP 2

Select your Cable (tick to select) ☒

 1kV (LV) Dbl Ins Orange/White 35mm ² - 172A <input type="checkbox"/> 50mm ² - 217A <input type="checkbox"/> 70mm ² - 273A <input type="checkbox"/> 95mm ² - 329A <input type="checkbox"/> 150mm ² - 450A <input type="checkbox"/>	 1kV (LV) Clear 1/0 - 250A <input type="checkbox"/> 2/0 - 300A <input type="checkbox"/> 4/0 - 400A <input type="checkbox"/>	 15kV (HV) Orange 1/0 - 250A <input type="checkbox"/> 4/0 - 400A <input type="checkbox"/>	 25kV (HV) Orange 1/0 - 250A <input type="checkbox"/> 2/0 - 300A <input type="checkbox"/>	 35kV (HV) Orange 1/0 - 250A <input type="checkbox"/>
--	--	---	---	--

Contact TEN if you require an AMP Rating not listed

Choose from the standard lengths of cable below (longer lengths available)

1 metre <input type="checkbox"/>	1.5 metres <input type="checkbox"/>	2 metres <input type="checkbox"/>	2.5 metres <input type="checkbox"/>	3 metres <input type="checkbox"/>
----------------------------------	-------------------------------------	-----------------------------------	-------------------------------------	-----------------------------------

STEP 3

Available Clamps (tick to select) ☒

 M12 hole LV only <input type="checkbox"/>	 M12 hole LV only <input type="checkbox"/>	 <input type="checkbox"/>	 <input type="checkbox"/>	 <input type="checkbox"/>	 <input type="checkbox"/>	 <input type="checkbox"/>
BPL12	USC12-H19	11190-A	11190	C600-0197	10476	13768-2
5-19mm, screwdriver handle, M12 hole LV Only	5-19mm, 19mm hex nut drive, M12 hole LV Only	Screw type, serrated jaw, 3-32mm, 400A, bolted ferrule, screwdriver handle, HASTINGS	Screw type, serrated jaw, 3-32mm, 400A, bolted ferrule, shot-gun ring, HASTINGS	Duckbill, snap-on, 4-38mm, 400A, threaded ferrule, shot-gun ring, CHANCE	Duckbill, snap-on, 4-30mm, 400A, threaded ferrule, shot-gun ring, HASTINGS	Gloving, clear, 4-25mm, 400A continuous, threaded ferrule, HASTINGS
Includes Lugs		Includes Ferrules				
 <input type="checkbox"/>		Jaw to eye style (J-E), welded to ratchet podger, folding handle TENA511		 <input type="checkbox"/>		Jaw to jaw style (J-J), welded to ratchet podger, folding handle TENA512

NOTE: Jumpers, Bonders and Clamp Assemblies are for "TEMPORARY USE ONLY" and should not be left exposed for extended periods in outdoor conditions

STEP 4

Email this form to sales@tengroup.com.au

