

[Enquire now](#)

Price on application

Row	stock_code	Desc
93	IBC17	ABC Bundle Restraint (Cat) MacLean
307	IBB65	ABC Bundle Restraint MacLean
127	IBB50	ABC Bundle restraint, 44.5mmOD non-metallic, Al Alloy Neoprene grip, RHL, MP
61	ABCHB20-325	ABC Hook Bolt M20 x 325mm, Galv, Maclean
101	ABCHB16-250	ABC Hook bolt, M16 x 250mm, galv,to drawing, Maclean
68	ABCHB20-300	ABC Hook bolt, M20 x 300mm, galv,to drawing, Maclean
246	ASG-SH-128934	ABC Hook, service fitting, 10mm, Maclean
527	ABCSC-435	ABC Suspension Clamp, 4 x35mm2, suit LVABC, A4-5023C,Maclean
580	ABCSC-470	ABC Suspension clamp, 4 x70mm2, suit LVABC, A4-5023C,Maclean
511	ABCTC-5095L	ABC Termination clamp, 4 x 50-95sqmm, Large R Clip, Maclean
366	ABCYB-12A	ABC Yoke bar 16mm, double suspension, 300mm spacing, 12kN MFL
491	AS-70-B	Anchor shackle M16 Bolt and Nut Only, 70kN, Dulhunty Power
566	LM73011	Anchor shackle, 120kN, bolt & nut, per AS1154, galv Maclean
226	AS-160-RX	Anchor shackle, 160kN, Charpysteel, Clevis pin, Maclean
696	AS-32-RX	Anchor shackle, 32kN, Charpysteel, Clevis pin, Maclean
609	AASC-100210H	Angle clamp, Aluminium, 10 -21mm with Hex pin, Maclean
621	AR-A 11.25	Armour Rod, Alum, 11.0 -11.8mm, AAC AAAC & ACSR, Black, Maclean
301	AR-CC 09.00	Armour Rod, Copper, 8.8-9.5mm,Cu, Red, Maclean
148	AR-S 04.80	Armour Rod, Steel, 4.6- 5.0mm,SC/GZ, Black, AR-S 04.80 R3,Maclean
414	ASC4-G	Bail Clamp, 7.0 - 18.8mm ODw/ 1 x M10 Galv Bolt, Maclean
168	BH-70-LS	Ball Hook 70kN Long Shank, Maclean
31	PB-500-2	BRACKET, 500mm POLE BAND,Galv, 3 BOLT, Maclean
259	EA-MB-66522	Bracket, mounting, 93mm x13mm x 3mm, for 100 amp service fuses - Energy Aus
575	EA-MB-66340	Bracket, Mounting, Guy Connection Plate, 195 x 75mm, M24, Maclean
690	EA-RS-H16083	Cable Saddle, Galv steel M14mm Holes to suit 250Dia round pole, 30mm OD UG Cable
399	EA-RS-H16148	Cable Saddle, Galv steel M14mm Holes to suit 250Dia round pole, 70mm OD UG Cable
118	EA-RS-65854	Cable Saddle, Galv steel, Flat mount 2 x M12mm Holes, MK1 SUIT 50mm ² 25mm OD Cable
699	EA-RS-151019	Cable Saddle, Galv steel, Flat mount 2 x M12mm Holes, MK6 suit 300mm ² 66mm OD Cable
351	HEX-57	Clevis pin, hexagonal, splitpin, 57mm, galv steel, Maclean
712	RPIN16X48B	Clevis Pin, M16 x 46mmwithout split pin and straps,galv, Maclean
694	RPIN16X55	Clevis Pin, Round (Pin only) with splitpin, 16mm x 55mmL, suit CTHI-1850
20	CTHI-1850	Clevis Thimble, Cast Iron,70kN round pin
692	CT-70X	Clevis tongue, 70kN, Charpy Steel, M16 bolt and nut with SS pin, 20mm opening, Maclean
693	CT-70	Clevis tongue, 70kN, Galv steel, M16 bolt and nut with SS pin, 20mm opening, Maclean
281	CLA2375F45	Compression Lug, Aluminium,23.75mm OD, 45 deg bend onFlat palm no.5, Maclean
574	CLA3375SO5U	Compression Lug, Aluminium,33.75mm OD, Straight Offsetpalm no.5 Undrilled, Maclean
553	CLA3375SO5	Compression Lug, Aluminium,33.75mm OD, Straight Offsetpalm no.5, 4 hole, Maclean
591	CMJ-PHOSPHORUS	Compression Midspan Joint, Full tension, Phosphorus,37/3.75, AAAC, MP
561	CMJ-ORIOLE	Compression Midspan, Full Tension, 30/7/0.1059,ACSR, ORIOLE, Maclean
274	556294-1	Connector, wedge, tap, shearbolt, main 21.742-24.206mm, tap 23.215-24.18mm, CPI
535	X-BRACE-06	Cross Arm Brace, 1050 x 50 x 6mm, Galvanised steel, 18mm holes, Maclean
572	X-BRACE-03	Cross Arm Brace, 800 x 50 x 6mm, Galvanised steel, 18mm holes, Maclean
129	DE-CC 08.25NC	Deadend , Helixon Copper Clad for 7.9-8.8mm OD HDC, Non-Cable Looped
727	DE-A 23.75NC	Deadend Al for AAC, AAAC, 23.0-24.0mm OD Non-Cable Looped
685	DE-A 05.25	Deadend Al for AAC, AAAC, 5.1 - 5.4mm, Purple, Cable looped,RH Lay, Maclean
613	DE-A 07.50	Deadend Al for AAC, AAAC, 7.4 - 7.6mm, Blue, Cable looped, RHLay, Maclean
63	DE-FT 11.25	Deadend, ACSR, Full tension,11.2 - 11.3mm, Black, RH Lay, Maclean
393	DE-FT 08.40	Deadend, ACSR, Full tension,8.3 - 8.5mm, White, RH Lay, Maclean
648	DE-SP 11.25	Deadend, Al Clad ST, 11.2-11.3mm ACSR, Single pce, Blk, Cable looped, RH Lay, Maclean
80	DE-AC 05.93L	Deadend, Al Clad ST, 5.8 -6.5mm, SC/AC, White, Cablelooped, LH Lay, Maclean
670	DE-SP 09.00	Deadend, Al Clad ST, 8.9-9.1mm ACSR, Single pce, Red,Cable looped, RH Lay, Maclean



[Enquire now](#)

Price on application

614	DE-OPGW-1300	Deadend, Al Clad Steel, OPGW,13.2 - 12.5mm , Cable looped,LH lay, Green, MacLean
362	DE-CCT180-11	Deadend, CCT, 24.1 - 25.7mm,11kV, Purple, Cable loop, RHLay, Maclean
157	DE-DI16	Deadend, double insulated service, to suit 16-35mm ² twisted cable, Maclean
745	DE-CC 05.10NC	Deadend, Helixon Copper Clad for 4.8-5.2mm OD HDC, Non-Cable Looped
698	DE-OPGW1220	Deadend, suit 12.0 - 12.5mm LHL OPGW, Maclean
407	IBC14	Deadend, termination, 21.2mm range, suit 14mm catenary plus 3.65 rods, Al Alloy, MP
28	ST-AC2450-76	Distribution Side Tie, Al Clad, 24.5mm-26.5mm, suit 76mm neck, rubber pad, Maclean
223	DT-AC0900-76	Distribution Tie, Al Clad for 9.0-10.0mm OD for 76mm neckInsulator
425	DT-AC1000-112	Distribution Tie, Al Clad, 9.9 - 11.2mm, 112mm neck, bluepurple, white, RHL, Maclean
578	DT-AC1125-76	Distribution Tie, Al Clad,11.25 - 12.6mm, 76mm neck,Yell/Black/Purple, RH lay, MP
700	DT-AC1875-76	Distribution Tie, Al Clad,18.0 - 19.0mm, 76mm neck,Blue/Black, RH lay, Maclean
313	DT-AC0525-76	Distribution Tie, Al Clad,5.2- 6.0mm, 76mm neck,Yellow/White, RH lay, Maclean
145	DT-AC0750-76	Distribution Tie, Al Clad,7.4- 7.7mm, 76mm neck, Blue,RH lay, Maclean
402	DT-CCT40-76	Distribution Tie, PVC Black,14.9 - 16.4mm, CCT, 40mm ² ,76mm neck, White, Maclean
378	ECB-1	Earth Clamp 16-35sqmm, MacLean
472	ECP-01	Earth Rod Clamp 16-35sqmm 26 MacLean
576	EB24-500F-150	Eye Bolt, Forged, 210kN, 500mm long, M24 x 150mm, Maclean
384	EB16-150F	Eye Bolt, M16 x 150mm, Forged, 1 x M16 nut, 70kN,100mm thread, Maclean
96	EB16-200F	Eye Bolt, M16 x 200mm, Forged, 1 x M16 nut, 70kN,100mm thread, Maclean
610	EB20-290LP	Eye Bolt, M20 x 290mm, w LinkPlate, Forged, 1 x M20 nut,120kN, Maclean
54	EB20-600LP	Eye Bolt, M20 x 600mm, w LinkPlate, Forged, 1 x M20 nut,120kN, Maclean
247	ABCEN-12	Eye Nut, M12, galvanised, fortwisted service mains, Maclean
173	EA-BH-89797	Fascia, Barge Board Hook, 6mm, Galv, Maclean
252	ASG-MB-H75044	Fuse Mounting Bracket, 30 degangle, Galv steel, Maclean
331	GG-P2520	Guy Guard, PVC, 2.0m solidtube, 22mm ID, Maclean
215	GL-S 13.75	Guy Lock, Steel, 19/2.75SC/GZ, RH lay, w/out lashingrod, White, Maclean
58	HSC-2450-BODY	Helixon Suspension Clamp Body with rubber insert to suit 24.5-25.0mm OD
374	DHSCR2625-660	HSC Reinforcing rods, Double - to suit 26.0 - 26.5 AAC, AAAC & ACSR Conductor 2895mm L
646	DHSCR-1625	HSC Reinforcing rods, Double, Al, 15.8 - 16.4mm, RH lay,AAC AAAC ACSR, Org, Maclean
469	DHSCR-1875	HSC Reinforcing rods, Double, Al, 18.6 - 19.1mm, RH Lay,AAC AAAC ACSR, Black, Maclean
482	CCT-165	Insulator 22kV Pin Post 12kN, 336mm Long, 534mm Creep, Grey, c/w M16X165 stud
244	C/150/7	Insulator Pin, 7kN, Head C,M20 x 165mm, 150mm stem,A4-5330B, Maclean
277	C/300/7	Insulator Pin, 7kN, Head C,M24 x 165mm, 300mm stem,A4-5333B, Maclean
363	SWANECK-15	Insulator Pin, Swan Neck, Galv Stee lpin, 15mm Diameter, Leadhead, Maclean
71	SHLV1	Insulator Reel, R1, 57mmOD, 54mmH, 9kN Transverse LoaMaclean
760	S16050037MXAL023	Insulator, 132kV polymer, long rod, Clevis Tongue, 18mm Holes
221	UG125BSPZ	Insulator, disc, glass, 125kN,BS, 280-146-450, Zn sleeve, 20, w clip, Dulhunty Power
508	UG160BLZ	Insulator, disc, glass, 160kN, ball& socket, zinc, 400mm creepage, Maclean
590	UG160BSZ	Insulator, disc, glass, 160kN,BS, 280-146-400, Zn sleeve, 20, w clip, Dulhunty Power
5	UG70TC	Insulator, disc, glass, 70kN, tongue & clevis, 320mm creepage, Maclean
510	UG70TCPZ	Insulator, disc, glass, 70kN,CT, 280-146-440, Zn sleeve, 16C, Dulhunty Power
185	KU-3	Ku Lugs Type 3 25-35sqmm, 10mm hole, MacLean
34	LG-A 26.25	Line Guard, suit 37/3.75 AAAC,25.9mm - 27.0mm, 1200mmL,black/red, Maclean
702	LS-AC 06.00L	Line Splice, Aluminium Clad,5.8 - 6.5mm, SC/AC, LH lay,White, Maclean
88	LS-A 10.20	Line Splice, Aluminium, 10.2- 10.5mm, AAC, AAAC, Purple, Maclean
634	LS-A 13.50	Line Splice, Aluminium, 13.3- 13.8mm, AAC, AAAC, Green, Maclean
571	LS-A 18.75	Line Splice, Aluminium, 18.60- 19.40mm, AAC, AAAC, Black, Maclean
628	LS-A 07.50	Line Splice, Aluminium, 7.50- 8.0mm, AAC, AAAC, Blue, Maclean
57	LS-A 14.30	Line Splice, Aluminium,13.9 -14.5mm, AAC, AAAC, Blue, Maclean
537	LS-CC 12.80	Line Splice, Copper Clad,12.6 -13.1mm, HDCu Copper, RHLay, Purple, Maclean
541	LS-CC 15.00	Line Splice, Copper Clad,15.0 -15.6mm, HDCu Copper, RHLay, Red, Maclean
347	LS-CC 18.30	Line Splice, Copper Clad,18.1-18.7mm, HDCu Copper, RHLay, Orange, Maclean
655	LS-S 04.80	Line Splice, Steel, 4.5 -4.9mm, SC/GZ, RH Lay, Black, Maclean
686	LS-S 06.00	Line Splice, Steel, 5.6 -6.1mm, SC/GZ, RH Lay, Yellow, Maclean



[Enquire now](#)

Price on application

8	LS-S 07.50	Line Splice, Steel, 7.35 -7.85mm, SC/GZ, RH Lay, Blue, Maclean
44	LP-120-500	Link Plate, 120kN, Galv Steel, 550mm hole centre, Maclean
741	CP28	Part, cap for screw anchorhub, Maclean
512	PGA-06185/2-NS	PG Clamp, Al, 10.0-18.0mmmain, 3.0- 10.0mm tap, 2x M10SS Bolts, Maclean
29	PGB-35300/3-N	PG Clamp, Bimetal, 12.5-22.0mm Al, 10.0-20.0mm Cu, 3 x M10 SS bolts, MP
569	HPSCR-2450	Pivot Support Rods, 24.5-25.0mm, AAC, AAAC, ACSR,OPGW, RH Lay, Purple, Maclean
620	PS16-250	Pole Step, 16 x 250mm, knockin type, Galvanised steel,Maclean
367	PS-16250-S	Pole Step, 16 x 250mm,Threaded, Screw in type,Galvanised steel, Maclean
589	SC27SG108-D	Polymer drop out fuse unit 22kV 100A continuous, 8kA interrupt, Maclean
471	DS-15M	Polymer Insulator, 15kV, 70kN, Tongue and Clevis, GalvPin, Creepage 391mm, Maclean
631	RR-OPGWA 1140	Reinforcing Rods, 11.4mm,OPGW, 2300mm L, Al Alloy, RHLay, Yellow, MP
303	RR-OPGW 1140S	Reinforcing Rods, 11.4mm,OPGW, 600mmL, 11.2 - 12.0mm, Al Clad, RH lay, Yellow, MP
135	DE-DI16-EPDM	Rubber insert, suit Service Dead End DI16 10-35mm2, EPDM Rubber, Maclean
132	ST-AC1125-76	Side Tie, 11.0-12.0mm, AlClad Steel, 76mm neck, Black,Maclean
197	ST-AC1750-76	Side Tie, 17.0 - 18.2mm, AlClad Steel, 76mm neck, Blue,Maclean
64	ST-AC1920-76	Side Tie, 19.0 - 20.5mm, AlClad Steel, 76mm neck, Black,Maclean
106	ST-AC2375-76	Side Tie, 22.0 - 24.0mm, AlClad Steel, 76mm neck,Green/Blue, Maclean
350	ST-CCT180-76	Side Tie, Plastic, CCT, 24.1-25.7mm, Purple, Black colour, Maclean
89	SBT-22	Split bolt, 16mm2, tinned,Maclean
290	LS-S 12.00	Steel Splice 7/4.00 SC/GZ 12mm Staywire
358	ZHP027-0C00100	Surge Arrestor 27kV 10kA Heavy DutyPolymer, w/C bracket, Maclean
588	ASG-ABC5B-66605	Suspension Bracket, Bundleconductor, Galv, 16 x 45mmClevis pin, Maclean
288	HSCR-1755	Suspension Clamp Rods, 17.6 -18.0mm, AAC, AAAC, ACSR, RHLay, Brown, Maclean
623	HSCR-1950L	Suspension Clamp Rods, 19.5 -20.2mm, AAC, AAAC, ACSR,OPGW, LH Lay, Orange, Maclean
283	HSC-1755-BODY	Suspension, body, rubber ins,17.6- 18.05mm, AAC AAAC ACSR,M16, SS pin,, Maclean
217	TH-70	Tongue Hook, 70kN, Galvanisedsteel, 18mm hole, Maclean
130	TET-70X	Twisted Eye Tongue, 70kN, 18mm hole, 16mm thick, CharpySteel, Maclean
97	UBOLT16-460	U-Bolt, 16mm x 460mm, 4 nuts& washers, Galv Steel, Maclean
506	4D20-31.1	Vibration damper, 4D20,suit 27.0mm-31.1mm conductor, M12 Gal St Bolts, Dulhunty
231	W24SQUARE	Washer, Flat M24 75mm x 75mm, Galvanised, Maclean
146	R5057	Wirelink Splice for gal wire,1.4mm - 2.6mm, Maclean
137	R5057V	Wirelink Splice for gal wire,1.4mm - 2.6mm, Maclean
232	R5065V	Wirelink Splice, splice to suit galwire 3.7mm -4.1mm, Maclean
279	R107	Wirelink Splice, automatic, suit Copper CU, 8.64mm - 9.78mm, Maclean
489	R5059	Wirelink Splice, for gal wire,2.3mm - 2.9mm, Maclean
332	R5058V	Wirewise, deadend for gal wire 2.3mm - 2.9mm, Maclean
260	R5064V	Wirewise, deadend suit galwire 3.7mm-4.2mm, withoutbail, Maclean